🔀 КУОСЕRа

A Device You Can Count On

The flexible paper handling options with up to 2,600 sheets and modern security features, combined with long-life components provides exceptional efficiency and reliability make the ECOSYS PA5500x the ideal choice to increase overall performance of workgroups. With a print speed of up to 55 pages per minute and a fast first print out, it's always ready when you need it.



GENERAL

KYOCERA ECOSYS Laser Monochrome Printer Operation panel: LCD 21 characters, 5 lines Type: Desktop Engine speed: Up to 55 pages A4 per minute; Duplex print speed: 39.5 page per minute, A4. Resolution: 1.200 x 1.200 dpi Recommended Ave rage Print Volume: 27,500 pages per month. Maximum Life: 1,000,000 pages or 5 years. Warm-up time: Approx. 25 seconds or less Time to first print: Approx. 4.5 seconds or less CPU: ARM Cortex-A53 Dual core 1.4GHz Memory: Standard 512MB; Max. 2.5GB (optional) Standard interfaces: Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1 000BaseT), optional W ireless LAN (IEEE 802.11b/g/n), 2 eKUIO slots for optional internal print server or SSD hard disc. Slot for optional SD/SDHC Card. Integrated accounting: 100 department codes. Dimensions (W x D x H): Without packaging: 380 x 410 x 320 mm (without protrusions); 390 x 416 x 343 mm (with protrusions); With packaging: 549 x 494 x 438 mm We ight: Approx. 16.1kg with bundled toner With packaging: 20 kg Power source: AC 220 ~ 240 V, 50/60 Hz Power consumption: Printing: 676.1 W Ready mode: 9 W Sleep-mode: 0.5 W Noise (sound pressure level: ISO 7779/ISO 9296): Printing 56 dB (A) Stand-by: 30 dB (A) Safety standards: TÜV/G S, CE This unit is manufactured according to ISO 9001 quality standard and ISO 1 4001 environmental standard.

PAPER HAN DLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOC ERA under normal environmental conditions. Input capacity: Multi-purpose tray: 100 sheets, 60 to 220 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (140 x 210 to 216 x 356 mm), Banner paper up to 915 mm. Standard universal paper cassette: 500 sheet, 60–120 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (140 x 210 to 216 x 356 mm). Max. input capacity with options: 2,600 sheets. Duplex: Standard duplex unit, 60 to 120 g/m², A4, A5, B5, Letter, Legal, Custom (140x 210 mm - 216 x 356 mm). Output capacity: 500-sheet-face-down with paper full sensor and optional 250-sheet-face-up with PT-320

PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL6 (5 c/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and Open XPS, PPML, TIFF/JPEG Direct Print Support, URF, PWG Raster, PCLm, IBM Proprinter, Line Printer, Epson LQ-850. Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Chrome OS, Linux, as well as other operating systems on request. Fonts/barcodes: 93 outline fonts (PCL6, KPDL3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode, 10 type of two-dimensional barc

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752. TK-343 4 Toner Kit: Microfine toner black for 25,000 pages A4. Capacity of starter toner is 10,000 pages A4.

OPTION

PF-3110 Paper feeder (max. 4 units): Max. 500 sheets, 60 - 120 g/m²; A4, A5, B5, Letter, Legal, Custom (92 x 162 mm - 216 x 356 mm) PF-3100 Bulk paper feeder and PB-325 Printer base: Max. 2,000 sheets, 60 - 220 g/m²; A4, A5, B5, Letter, Custom (76 x 148 to 216 x 305 mm); not to be combined with PF-3110 PT-320 Paper tray: 250-sheet face-up output tray CB-360W Cabi net: High Cabinet for 2 draw configuration, Approx. 380 x 411 x 508 mm (WxDxH) CB-365W Cabinet: Low cabinet for 4 draw configuration, Approx. 380 x 411 x 254 mm (WxDxH) CA-3100 Caster Unit: for increased stability. Mandatory when installing 4 optional paper feeders. Memory up grade: MM-20(1GB)/MM-21(2GB) Storage Devices for easy document manag ement: HD-17 SSD hard disk: 64GB HD-18 SSD hard disk: 256GB

SECURITY

UG-33 AC : ThinPrint s upport UG-33 AC : ThinPrint s upport UG-35 C: TPM (Trusted Platform Module) USB IC Card Reader + Card Authentication Kit (B) AC : Support for various authentication keys available. CRH 10: IC card Reader Holder . Optional interface: IB-32: B: IEEE 1284 interface IB-37: Wireless LAN (802.11b/g/n) with Wi-Fi Direct IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/1,000 BaseT IB-51: Wireless LAN Interface (802.11b/g/n)

WARRANTY

2 years on-site as standard .

WHAT'S IN THE BOX:


Main unit, pre-installed starter toner, waste toner box, u ser documents, power supply cord.

ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.

(Wi/Fi)



MARCH2023ECO SYSPA5500x/VER1.0



AirPrint

mopria

KYOCER A Document Solutions Australia



Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. ©2022 KYOCERA Document Solutions AU & NZ