MAXIFY GX4060 MegaTank

TECHNICAL SPECIFICATIONS





MAXIFY GX4060 **Mega**Tank



ENJOY ECONOMICAL HIGH-YIELD PRINTING

Comprising of Canon's new MegaTank ink technology, the MAXIFY GX4060 MegaTank is capable of printing up to 6,000 page in black, and up to 14,000 pages in colour¹, reducing the chances that you will run out of ink when you need it most. Canon's Economy printing mode will also enable you to decrease printing costs and maximise your productivity even further by reducing the consumption of ink, achieving yields of up to 9,000 in black, and up to 21,000 in colour.



SUPER CHARGED PRODUCTIVITY

The MAXIFY GX4060 MegaTank has a large paper capacity. The Front Cassette holds 250 sheets of plain paper while the Rear Tray can handle 100 sheets of plain paper. Collectively this printer has a capacity of 350 sheets – you will spend less time refilling your printer.



GET THE BENEFIT OF EASY MAINTENANCE

The MAXIFY GX4060 MegaTank offers the benefit of a user replaceable Print head, Maintenance Cartridge and a Paper Roller which can be easily cleaned. With the convenience of being able to easily maintain it yourself, it means less downtime with printing.



ALL-IN-ONE PRINTING FOR YOUR BUSINESS MEDIA NEEDS

In addition to delivery high-quality documents, MAIXFY MegaTank printers offer compatibility with a wide range of media types and sizes. With the MAXIFY GX4060 MegaTank you can now also print thick, rigid paper up to 0.7mm thick such as posterboard. Now create personalised posters for your business easily.



'Approx. yields are based on Canon original method using test patterns ISO/IEC 24712 (Colour chart). The estimated page yields are determined not based on the initial set of bundled ink bottles, but based on subsequent sets of ink bottles after print head nozzles have been filled with ink from the initial set of ink bottles. Black and colour page yields are not to be combined. Page yields varies significantly depending on contents printed and other factors. ²Economy mode plain paper Page Yield is an estimate.

³AirPrint and Mopria are available for download via the Apple Store (iOS) and Play Store (Android).

What inks can I use with my printer?

GI-66BK GI-66C GI-66M GI-66Y



Maintenance Cartridge

MC-G03





SPECIFICATIONS

GENERAL FEATURES			
Model	MAXIFY GX4060 MegaTank		
Ink Type	4 Bottles (PGBK / C / M / Y)		
Maximum Print Resolution	600 dpi x 1,200 dpi*1		
Size	Approx. 399 x 417 x 251mm		
	Approx. 15.8 x 16.4 x 9.9 inch		
Weight	Approx. 9.5 kg Approx. 20.9 lbs		
Display	2.7" / 6.7 cm LCD (Monochrome)		
Interface	USB / Wireless		
	Wireless 2.4GHz & 5GHz, Wireless Direct, Wired LAN,		
Connectivity	Mobile		
Input Power	AC 100-240 V, 50 / 60 Hz		
PRINT SPEED			
Document: Colour*2	Approx. 13.0 ipm		
Document: Black & White*2	Approx. 18.0 ipm		
POWER CONSUMPTION			
Copying*3 USB connection to PC	Approx. 20W		
OFF	Approx. 0.1 W		
Standby (MFP: scanning lamp is off) USE connection to PC	Approx. 0.9 W		
Standby (all ports connected, MFP: scanning lamp is off)	Approx. 1.4 W		
Time to enter Standby mode	Approx. 5 min		
ENVIRONMENT			
Operating Environment*4	Temperature: 5 - 35 °C Humidity: 10 - 90 %RH (no dew condensation)		
Recommended Environment*5	Temperature: 15 -30 °C Humidity: 10 - 80 %RH (no dew condensation)		
Storage Environment	Temperature: 0 - 40 °C Humidity: 5 - 95 %RH (no dew condensation)		
ACOUSTIC NOISE (PC PRINT)			
Quiet Mode	Available		
Acoustic Noise (PC print) Plain Paper*6	Approx. 49.0 dB(A)		
PRINT HEAD / INK			
Number of Nozzles	Total 4,352 nozzles (BK: 1,280 nozzles, C/M/Y 1,024 nozzles)		
Compatible Inks	GI-66BK, GI-66C, GI-66Y, GI-66M		
PRINTABLE WIDTH			
	Up to 206 mm (8 inch)		




PRINTABLE AREA		
Bordered Printing	 #10 Envelope, DL Envelope, Envelope C5, Monarch Envelope Top: 12.7 mm, Bottom: 12.7 mm, Right: 5.6 mm, Left: 5.6 mm 4" x 6", 5" x 7", 7" x 10", 8" x 10" Top: 3 mm, Bottom: 5 mm, Right: 3.4 mm, Left: 3.4 mm Square(127 mm x 127 mm) Top: 6 mm, Bottom: 6 mm, Right: 6 mm, Left: 6 mm Other Top: 5 mm, Bottom: 5 mm, Right: 5 mm, Left: 5 mm Bordered Auto 2-sided printing Top: 5 mm, Bottom: 5 mm, Right: 5 mm, Left: 5 mm 	
SUPPORT MEDIA		
Rear Tray	Plain Paper (64 g/m2 - 105 g/m2), High Resolution Paper (HR-101N), Photo Paper Plus Glossy II (PP-301), Photo Paper Pro Luster (LU-101), Photo Paper Plus Semi-gloss (SG-201), Photo Paper Glossy (GP-701), Matte Photo Paper (MP-101), Envelope, Magnetic Photo Paper(MG-101), Restickable Photo Paper(RP-101), Light Fabric Iron on Transfers(LF-101), Double sided Matte Paper(MP-101D)	
Cassette	Plain Paper (64 g/m2 - 105 g/m2)	
Rear Flat Tray	Paperboard	
PAPER SIZE		
Rear Tray	A4, A5, A6, B5, LTR, LGL, B-Oficio, M-Oficio, Foolscap, FS, Executive, #10 Envelope, DL Envelope, C5 Envelope, Monarch Envelope, Card Size (91 mm x 55 mm), 4" x 6", 5" x 7", 7" x 10", 8" x 10", Square (127 mm x 127 mm), Custom size (width: 89 mm - 216 mm, length: 127 mm - 1,200 mm) A4, A5, B5, LTR, Executive [Custom size] width 148 mm - 215.9 mm,	
Cassette	length 210 mm - 297 mm	
Rear Flat Tray	A4, B5, LTR [Custom size] width 89 mm - 215.9 mm, length 127 mm - 1,200 mm	
PAPER HANDLING (MAXIMUM NUMBER)		
Rear Tray	Plain Paper (64 g/m2): 100, High Resolution Paper (HR-101N): 80. 4" x 6" - Photo Paper Plus Glossy II (PP-301), Photo Paper Plus Semi-gloss (SG-201), Photo Paper Glossy (GP-701): 20. Matte Photo Paper (MP-101), Magnetic Photo Paper(MG-101), Restickable Photo Paper(RP-101): 1. 5" x 7" - Photo Paper Plus Glossy II (PP-301), Photo Paper Plus Semi-gloss (SG-201): 10	
Cassette	Plain Paper (64 g/m2): 250	
Auto Document Feeder	Plain Paper (64 g/m2): 35 LGL: 5, others: 1	
Rear Flat Tray	1	
PAPER WEIGHT		
Rear Tray	Plain Paper: 64 g/m2 -105 g/m2, Canon paper: max paper weight : approx. 265 g/m2, Photo Paper Plus Glossy II (PP-301)	
Cassette	Plain Paper: 64 g/m2 -105 g/m2	
Rear Flat Tray	Paper Thickness : 0.1 mm to 0.7 mm	



SCANNER FUNCTIONS*7 Scanner Type Flatbed (ADF / Platen) Optical Resolution*8 1,200 x 2,400 dpi Scanning Bit Depth (Input/Output) Grayscale: 16 bit / 8 bit Colour: RGB each 16 bit / 8 bit Maximum Document Size A4 / LTR (216 x 297 mm)	
Optical Resolution*8 1,200 x 2,400 dpi Scanning Bit Depth (Input/Output) Grayscale: 16 bit / 8 bit Colour: RGB each 16 bit / 8 bit	
Scanning Bit Depth (Input/Output) Grayscale: 16 bit / 8 bit Colour: RGB each 16 bit / 8 bit	
Colour: RGB each 16 bit / 8 bit	
Maximum Document Size A4 / LTR (216 x 297 mm)	
COPY FUNCTIONS	
Maximum Document Size A4 / LTR	
Plain Paper (64 g/m2 - 105 g/m2), Photo Paper F 301), Photo Paper Pro Luster (LU-101), Photo Paper (SG-201), Photo Paper Glossy (GP-701), Matte Ph Light Fabric Iron on Transfers (LF-101)	per Plus Semi-gloss
Image Quality 3 positions (Economy, Standard, High)	
Multiple Copy Black & White / Colour: max. 99 pages	
FAX	
Applicable Line PSTN	
Transmission Speed*9 Black: Approx. 3 sec Colour: Approx. 1 min	
Black: Standard - 8pels/mm x 3.85 lines/mm. Fir lines/mm. Extra Fine - 300 dpi x 300 dpi. Colour: 200 dpi ×200 dpi	1е - 8pels/mm x 7.7
Print Size A4, LTR, LGL	
Scanning Width A4, LTR	
Modern Speed Maximum 33.6 kbps (Automatic fall back)	
PRINTING SOLUTION	
AirPrint / Mopria / Canon Print Service (for Andro Available for* ¹⁰ Link / Canon PRINT Inkjet/SELPHY (for iOS / Andro	•
Direct	
Direct Windows ^R 11, 10, 8.1, 7SP1. Windows Server 2022 R2/2008 R2 SP1. macOS 10.14.6 ² 12	2/2019/2016/2012
Windows ^R 11, 10, 8.1, 7SP1. Windows Server 2022	2/2019/2016/2012

What's in the Box?

Printer Power Cord Full set of Starter Ink bottles Getting started guide





- *1: Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- *2: Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734.
- *3: Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings. Specifications are subject to change without notice.
- *4: The performance of the printer may be reduced under certain temperature and humidity conditions.
- *5: For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.
- *6: Acoustic Noise is measured based on ISO7779 standard with default setting.
- *7: TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
- *8: Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.
- *9: Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart. Color document fax transmission speed is based on default setting using Canon Color Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- *10: Resolution may be changed between Direct print and printing from PC.

Standard disclaimers:

- If your inkjet printer is found defective within the applicable manufacturer warranty period (1 Year), we'll replace it with the same, or an equivalent model. Excludes damage caused by external factors. Canon's full replacement promise is in addition to your rights under Australian Consumer Law which, depending on the type of fault, includes repair, replacement or a refund. For full terms see: www.canon.com.au/printassist or the card in the printer box. Only for products purchased at Authorised Canon Australia retailers
- Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and
 does not take into account data processing time on host computer. Print speed may vary depending on
 system configuration, interface, software, document complexity, print mode, page coverage, type of paper
 used etc.
- Approx. yields are based on Canon original method using test patterns ISO/IEC 24712 (Colour chart). The
 estimated page yields are determined not based on the initial set of bundled ink bottles, but based on
 subsequent sets of ink bottles after print head nozzles have been filled with ink from the initial set of ink
 bottles. Black and colour page yields are not to be combined. Page yields varies significantly depending on
 contents printed and other factors.
- Economy mode plain paper Page Yield is an estimate.
- AirPrint and Mopria are available for download via the Apple Store (iOS) and Play Store (Android).
- USB cable not included.

Note: Ink must be available in each ink-tank for all functions including copy, print and scan. Some functions may not work unless an internet connection established.





www.canon.com.au www.canon.co.nz